



专利产品 Patented Product 2025-Version







Typical Mating Sequence










3D View



Recommended P.C.B Layout(Top View)

Tolerance ±0.05


Notes:

1. Material Specification:
   1-1. Housing: High Temperature Thermoplastic. UL94 V-0, Black;
   1-2. Contact: High Conductivity Copper Alloy;
2. Plating Specification:
   2-1. Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 80μ" min. Nickel overall;
3. Electrical performance:
   3-1. Voltage Rating: 250v DC/power blade, 120v DC/signal pin;
   3-2. Current Rating: 60A (per pair power blade), 3A (per signal pin).
   3-3. LLCR:
   initial 0.6mΩ max., finished 1.0mΩ maximum change.(per pair power blade);
   initial 10mΩ max., finished 20mΩ maximum change.(per signal pin).
   3-4. Dielectric Withstanding Voltage:
   1500v DC rms/power blade; 500v DC rms/signal pin.
   3-5. Insulation Resistance:
   5000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   4-1. Insertion Force: 19.6N (2.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 4.5~11N (0.4~1.2kgf)/Per Pair;
   4-3. Durability Life: 10,000 cycles. max.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Operating Temperature rang: -40~125°C.
7. All parts RoHS and Reach compliant.
8. ※ See SPS-PDC-06 for Terminal details.


THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION


GENERAL TOLERANCES UNLESS SPECIFIED				PART NO.	Prolanv®
.X ±	0.30	X.° ±	3°	PDC0210F0001	
.XX ±	0.20	.X° ±	2°	APPROVED BY: Henry	TITLE: EN60A series | Power Female. 4PW+6S, Straight Type
.XXX ±	0.05	.XX° ±	1°		
CUSTOMER DRAWING				CHECKED BY: Poplar	DWG NO. PDC02-10
SIZE	UNITS			DRAWN BY: Kaylee	SHEET: 1 / 2 · SCALE: 1:1 · REV: B2
A4	mm[only]				

Copyright Prolanv Inc. www.prolanv.com





30 Pcs/Tray





Total: 2x5 Layers





Notes:

1. Q'ty:30 Pcs/Tray, 2x5 Layers=300 Pcs/Carton.
2. Tray Pallet size: 332*162mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
.X ± 0.30	X.° ± 3°	PDC0210F0001	
.XX ± 0.20	X° ± 2°	APPROVED BY: Henry	TITLE: EN60A series | Power Female. 4PW+6S, Straight Type, Packaging
.XXX ± 0.05	.XX° ± 1°		
CUSTOMER DRAWING		CHECKED BY: Poplar	DWG NO.: P-PDC02-10
SIZE: A4	UNITS: mm[only]	DRAWN BY: Kaylee	SHEET: 2 / 2 | SCALE: NA | REV: A4

Copyright **Prolanv** Inc. www.prolanv.com