



专利产品 Patented Product





Typical Mating Sequence












3D View



Recommended P.C.B layout (Top View)
Tolerance ±0.05

Part Number: PDC1910F0003

- Optional Long Power blade 可选项 长电源P组数 | Pairs Code: 1~9 & A~C
- Long Power blade 长电源P组 | 起始位 Start location code: 1~9 & A~C
- Long Power blade 长电源P组 | 终止位 End location code: 1~9 & A~C

Notes:
1. Material Specification:
   1-1. Housing: High Temperature Thermoplastic. UL94 V-0, Black;
   1-2. Contact: High Conductivity Copper Alloy;
   1-3. Metal Rod: Alloy.
2. Plating Specification:
   2-1. Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 80μ" min. Nickel overall;
   2-2. Metal Rod: Nickel overall.
3. Electrical performance:
   3-1. Voltage Rating: 250v DC/power blade, 120v DC/signal pin;
   3-2. Current Rating: 60A/Per pair power blade, 3A/Per Signal Pin.
   3-3. LLCR:
   initial 0.6mΩ max., finished 1.0mΩ maximum change.(per pair power blade);
   initial 10mΩ max., finished 20mΩ maximum change.(per signal pin).
   3-4. Dielectric Withstanding Voltage:
   1500v DC rms/power blade; 500v DC rms/signal pin.
   3-5. Insulation Resistance:
   5000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   4-1. Insertion Force: 19.6N (2.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 4.5~11N (0.4~1.2kgf)/Per Pair;
   4-3. Durability Life: 10,000 cycles. max.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Operating Temperature rang: -40~125°c.
7. All parts RoHS and Reach compliant.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			
.X± 0.30		X.°± 3°	
.XX± 0.20		.X°± 2°	
.XXX± 0.05		.XX°± 1°	
CUSTOMER DRAWING			
SIZE	UNITS		
A4	mm[only]		

PART NO.	PDC1910F0003
APPROVED BY	Henry
CHECKED BY	Mike
DRAWN BY	Yang


Prolanv®

TITLE: EN60A series | Power Male. 8PW+6S, R/A DIP Type


DWG NO. PDC19-03

SHEET	SCALE	REV
1 / 2	1:1	A0


Copyright Shenzhen **Prolanv** Inc. www.prolanv.com




15pcs/Tray




Total 2*3 Layers











Notes:

1. Q'ty: 15Pcs/Tray, 2x3 Layers=90 Pcs/Carton.
2. Tray Pallet size: 332*162*17mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION	GENERAL TOLERANCES UNLESS SPECIFIED: .X ± 0.20, .XX ± 0.10, .XXX ± 0.05, X.° ± 3°, .X° ± 2°, .XX° ± 1°	PART NO. PDC1910F0003	Prolanv®
		APPROVED BY Henry	TITLE EN60A series | Power Male 8PW+6S, R/A DIP Type, Packaging
	CUSTOMER DRAWING	CHECKED BY Mike	DWG NO. P-PDC19-03
	SIZE: A4; UNITS: mm[only]	DRAWN BY Yang	SHEET: 2 / 2; SCALE: NA; REV: A0

Copyright Shenzhen **Prolanv** Inc. www.prolanv.com