




专利产品 2025-Version
Patented Product

















Notes:
1. Material Specification:
   1-1. Housing: High Temperature Thermoplastic. UL94 V-0, Black,
   1-2. Contact: High Conductivity Copper Alloy,
   1-3. Metal Rod: Alloy.
2. Plating Specification:
   2-1. Contact: Gold plating on Contact area, Matte Tin 80μ" min.
   on Tails, and 80μ" min. Nickel overall;
   2-2. Metal Rod: Nickel overall.
3. Electrical performance:
   3-1. Voltage Rating: 250v DC/power blade.
   3-2. Current Rating: 60A (per pair power blade).
   3-3. LLCR:
   initial 0.6mΩ max., finished 1.0mΩ maximum change.(per pair power blade).
   3-4. Dielectric Withstanding Voltage:
   1500v DC rms/power blade.
   3-5. Insulation Resistance:
   5000 MΩ min/Power blade.
4. Mechanical Performance:
   4-1. Insertion Force: 19.6N (2.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 4.5~11N (0.4~1.2kgf)/Per Pair;
   4-3. Durability Life: 10,000 cycles. max.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°C.
6. Operating Temperature rang: -40~125°c.
7. All parts RoHS and Reach compliant.
8. ※ See SPS-PDC-06 for Terminal details.

Part Number: PDC2920F0002

- Optional Long Power blade 可选项 长电源P组数 | Pairs Code: 1~9 & A~C
- Long Power blade 长电源P组 | 起始位 Start location code: 1~9 & A~C
- Long Power blade 长电源P组 | 终止位 End location code: 1~9 & A~C

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			
.X±	0.30	X.°±	3°
.XX±	0.20	.X°±	2°
.XXX±	0.05	.XX°±	1°
CUSTOMER DRAWING			


SIZE	UNITS
A4	mm[only]

PART NO.	PDC2920F0002
APPROVED BY	Henry
CHECKED BY	Poplar
DRAWN BY	Kaylee
TITLE	EN60A series | Power Male. 12PW, Straight Type
DWG NO.	PDC29-22


SHEET	SCALE	REV
1 / 2	1:1	A1

Prolanv®


Copyright Shenzhen **Prolanv** Inc. www.prolanv.com




15pcs/Tray



Total 2*4 Layers





Notes:


1. Q'ty: 15Pcs/Tray, 2x4 Layers=120 Pcs/Carton.
2. Tray Pallet size: 332*162*17mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			PART NO.	Prolanv®
X ± 0.20	X.° ± 3°		PDC2920F0002	
.XX ± 0.10	.X° ± 2°		APPROVED BY Henry	TITLE EN60A series | Power Male. 12PW, Straight Type Packaging
.XXX ± 0.05	.XX° ± 1°			
CUSTOMER DRAWING			CHECKED BY Poplar	DWG NO. P-PDC29-22
SIZE	UNITS		DRAWN BY Kaylee	SHEET 2 / 2 | SCALE NA | REV A1
A4	mm[only]			

Copyright Shenzhen **Prolanv** Inc. www.prolanv.com

EN60A series marks upgraded



Copyright **Prolanv** Inc. www.prolanv.com