




专利产品 2025 version
Patented Product

















Notes:
1. Material Specification:
   1-1. Housing: High Temperature Thermoplastic. UL94 V-0, Black;
   1-2. Contact: High Conductivity Copper Alloy;
   1-3. Metal Rod: Alloy.
2. Plating Specification:
   2-1. Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 80μ" min. Nickel overall;
   2-2. Metal Rod: Nickel overall.
3. Electrical performance:
   3-1. Voltage Rating: 250v DC/power blade, 120v DC/signal pin;
   3-2. Current Rating: 60A/Per pair power blade, 3A/Per Signal Pin.
   3-3. LLCR:
   initial 0.6mΩ max., finished 1.0mΩ maximum change.(per pair power blade);
   initial 10mΩ max., finished 20mΩ maximum change.(per signal pin).
   3-4. Dielectric Withstanding Voltage:
   1500v DC rms/power blade; 500v DC rms/signal pin.
   3-5. Insulation Resistance:
   5000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   4-1. Insertion Force: 19.6N (2.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 4.5~11N (0.4~1.2kgf)/Per Pair;
   4-3. Durability Life: 10,000 cycles. max.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Operating Temperature rang: -40~125°c.
7. All parts RoHS and Reach compliant.

Part Number: PDC2710F0003

Optional Long Power blade
可选项 长电源P组数 | Pairs
Code: 1~9 & A~C


Long Power blade
长电源P组 | 起始位
Start location code: 1~9 & A~C

Long Power blade
长电源P组 | 终止位
End location code: 1~9 & A~C


THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED				PART NO.	Prolanv®
.X±	0.30	X.°±	3°	PDC2710F0003	
.XX±	0.20	.X°±	2°	APPROVED BY: Henry	TITLE: EN60A series | Power Male. 8PW+12S, R/A DIP Type
.XXX±	0.05	.XX°±	1°		
CUSTOMER DRAWING				CHECKED BY: Poplar	DWG NO. PDC27-03
SIZE	UNITS			DRAWN BY: Kaylee	SHEET: 1 / 2 · SCALE: 1:1 · REV: A1
A4	mm[only]				


Copyright **Prolanv** Inc. www.prolanv.com




15pcs/Tray



Total 2*3 Layers









Notes:

1. Q'ty: 15 Pcs/Tray, 2x3 Layers=90 Pcs/Carton.
2. Tray Pallet size: 332*162*17mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
.X ± 0.20	X.° ± 3°	PDC2710F0003	
.XX ± 0.10	X° ± 2°	APPROVED BY: Henry	TITLE: EN60A series | Power Male 8PW+12S, R/A DIP Type, Packaging
.XXX ± 0.05	.XX° ± 1°		
CUSTOMER DRAWING		CHECKED BY: Poplar	DWG NO.: P-PDC27-03
SIZE: A4	UNITS: mm[only]	DRAWN BY: Kaylee	SHEET: 2 / 2 · SCALE: NA · REV: A1

Copyright **Prolanv** Inc. www.prolanv.com