



专利产品 Patented Product 2025-version





Typical Mating Sequence














Part Number: PDC2110F0003

- Optional Long Power blade 可选项 长电源P组数 | Pairs Code: 1~9 & A~C
- Long Power blade 长电源P组 | 起始位 Start location code: 1~9 & A~C
- Long Power blade 长电源P组 | 终止位 End location code: 1~9 & A~C


Notes:

1. Material Specification:
   - 1-1. Housing: High Temperature Thermoplastic. UL94 V-0, Black;
   - 1-2. Contact: High Conductivity Copper Alloy;
   - 1-3. Metal Rod: Alloy.
2. Plating Specification:
   - 2-1. Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 80μ" min. Nickel overall;
   - 2-2. Metal Rod: Nickel overall.
3. Electrical performance:
   - 3-1. Voltage Rating: 250v DC/power blade, 120v DC/signal pin;
   - 3-2. Current Rating: 60A/Per pair power blade, 3A/Per Signal Pin.
   - 3-3. LLCR: initial 0.6mΩ max., finished 1.0mΩ maximum change.(per pair power blade); initial 10mΩ max., finished 20mΩ maximum change.(per signal pin).
   - 3-4. Dielectric Withstanding Voltage: 1500v DC rms/power blade; 500v DC rms/signal pin.
   - 3-5. Insulation Resistance: 5000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   - 4-1. Insertion Force: 19.6N (2.0kgf) max./Per Pair;
   - 4-2. Withdrawal Force: 4.5~11N (0.4~1.2kgf)/Per Pair;
   - 4-3. Durability Life: 10,000 cycles. max.
5. IR Reflow: The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Operating Temperature rang: -40~125°c.
7. All parts RoHS and Reach compliant.


THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED				PART NO.	Prolanv®
.X±	0.30	X.°±	3°	PDC2110F0003	
.XX±	0.20	.X°±	2°	APPROVED BY: Henry	TITLE: EN60A series | Power Male. 10PW+12S, R/A DIP Type
.XXX±	0.05	.XX°±	1°		
CUSTOMER DRAWING				CHECKED BY: Poplar	DWG NO. PDC21-03
SIZE	UNITS			DRAWN BY: Kaylee	SHEET: 1 / 2 · SCALE: 1:1 · REV: A1
A4	mm[only]				


Copyright **Prolanv** Inc. www.prolanv.com





15pcs/Tray




Total 2*3 Layers











Notes:

1. Q'ty: 15 Pcs/Tray, 2x3 Layers=90 Pcs/Carton.
2. Tray Pallet size: 332*162*17mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
.X± 0.20	.X°± 3°	PDC2110F0003	
.XX± 0.10	.X°± 2°	APPROVED BY Henry	TITLE EN60A series | Power Male 10PW+12S, R/A DIP Type, Packaging
.XXX± 0.05	.XX°± 1°		
CUSTOMER DRAWING		CHECKED BY Poplar	DWG NO. P-PDC21-03
SIZE A4	UNITS mm[only]	DRAWN BY Kaylee	SHEET 2 / 2 · SCALE NA · REV A1

Copyright **Prolanv** Inc. www.prolanv.com