


专利产品 Patented Product




3D View




Mating View





Typical contact Sequence







Recommended P.C.B layout (Top View)
Tolerance ±0.05





Recommended Module case cutout size
建议机壳匹配的开孔尺寸





Notes:

1. Material Specification
   - 1-1.Housing: High Temperature Thermoplastic, UL94 V-0,
   - 1-2.Contact: High Conductivity Copper Alloy,
   - 1-3.Screw-Hole: Copper Alloy.
2. Plating Specification
   - Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 100μ" min. Nickel overall;
3. Electrical performance
   - 3-1. Voltage Rating: 125v DC max./power blade, 36v DC/signal pin;
   - 3-2. Current Rating: 20A max./Per pair power blade, 4A/Per Signal Pin.
   - 3-3. LLCR:
     - initial 0.5mΩ max., finished 1.0mΩ maximum change.(per pair power blade);
     - initial 10mΩmax., finished 20mΩ maximum change.(per signal pin).
   - 3-4. Dielectric Withstanding Voltage: 500v AC (RMS) for 60S
   - 3-5. Insulation Resistance: 1000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   - 4-1. Insertion Force: 9.8N (1.0kgf) max./Per Pair;
   - 4-2. Withdrawal Force: 3.5~8.5N (0.35~0.86kgf)/Per Pair;
   - 4-3. Durability Life: 3,000 cycles.
5. IR Reflow:
   - The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Waterproof Level ⩾IPX6 in the mated connector module state.
7. Operating Temperature Range: -40~125°c(without loss function).
8. All parts RoHS and Reach compliant.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			
.X± 0.30		X.°± 3°	
.XX± 0.20		.X°± 2°	
.XXX± 0.10		.XX°± 1°	
CUSTOMER DRAWING			
SIZE	UNITS		
A4	mm[only]		


PART NO.	PDC6210C0001
APPROVED BY	Henry
CHECKED BY	Poplar
DRAWN BY	Bing

Prolanv®


TITLE	SHEET	SCALE	REV
EN20A series | Power Female R/A DIP Type. 8PW+24S	1 / 2	1:1	A2

DWG NO. PDC62-10

Copyright Shenzhen Prolanv Inc. www.prolanv.com





20Pcs/Tray




Total: 2x8Layers

PE Film







Notes:

1. Q'ty:20 Pcs/Tray, 2x8 Layers=320 Pcs/Carton.
2. Tray Pallet size: 340*170mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
X± 0.30	X.°± 3°	PDC6210C0001	
.XX± 0.20	.X°± 2°	APPROVED BY: Henry	TITLE: EN20A series | Power Female R/A DIP Type. 8PW+24S Packaging
.XXX± 0.10	.XX°± 1°		
CUSTOMER DRAWING		CHECKED BY: Poplar	DWG NO.: P-PDC62-10
SIZE: A4	UNITS: mm[only]	DRAWN BY: Bing	SHEET: 2 / 2 · SCALE: NA · REV: A2

Copyright Shenzhen **Prolanv** Inc. www.prolanv.com