


专利产品 Patented Product




3D View





Mating View




Typical contact Sequence









Recommended P.C.B layout (Top View)
Tolerance ±0.05



Recommended Module case cutout size
建议机壳匹配的开孔尺寸






Notes:

1. Material Specification
   1-1.Housing: High Temperature Thermoplastic, UL94 V-0,
   1-2.Contact: High Conductivity Copper Alloy,
   1-3.Screw-Hole: Copper Alloy.
2. Plating Specification
   Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 100μ" min. Nickel overall;
3. Electrical performance
   3-1. Voltage Rating: 125v DC max./power blade, 36v DC/signal pin;
   3-2. Current Rating: 20A max./Per pair power blade, 4A/Per Signal Pin.
   3-3. LLCR:
   initial 0.5mΩ max., finished 1.0mΩ maximum change.(per pair power blade);
   initial 10mΩmax., finished 20mΩ maximum change.(per signal pin).
   3-4. Dielectric Withstanding Voltage: 500v AC (RMS) for 60S
   3-5. Insulation Resistance: 1000 MΩ min/Power blade; 500 MΩ min/Signal Pin.
4. Mechanical Performance:
   4-1. Insertion Force: 9.8N (1.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 3.5~8.5N (0.35~0.86kgf)/Per Pair;
   4-3. Durability Life: 3,000 cycles. max.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Waterproof Level ⩾IPX6 in the mated connector module state.
7. Operating Temperature Range: -40~125°c(without loss function).
8. All parts RoHS and Reach compliant.


THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION


GENERAL TOLERANCES UNLESS SPECIFIED				PART NO.	Prolanv®
.X±	0.30	X.°±	3°	PDC6610C0001	
.XX±	0.20	.X°±	2°	APPROVED BY: Henry	TITLE: EN20A series | Power Female R/A DIP Type. 12PW+12S
.XXX±	0.10	.XX°±	1°		
CUSTOMER DRAWING				CHECKED BY: Poplar	DWG NO.: PDC66-10
SIZE	UNITS			DRAWN BY: Bing	SHEET: 1 / 2 · SCALE: 1:1 · REV: A2
A4	mm[only]				

Copyright Shenzhen Prolanv Inc. www.prolanv.com




20 Pcs/Tray





Total: 2x8Layers



Notes:

1. Q'ty:20 Pcs/Tray, 2x8 Layers=320 Pcs/Carton.
2. Tray Pallet size: 340*170mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			PART NO.	Prolanv®
X ± 0.30	X.° ± 3°		PDC6610C0001	
.XX ± 0.20	.X° ± 2°	APPROVED BY Henry		TITLE EN20A series | Power Female R/A DIP Type. 12PW+12S Packaging
.XXX ± 0.10	.XX° ± 1°			
CUSTOMER DRAWING		CHECKED BY Poplar		DWG NO. P-PDC66-10
SIZE	UNITS	DRAWN BY Bing		SHEET 2 / 2 · SCALE NA · REV A2
A4	mm[only]			

Copyright Shenzhen Prolanv Inc. www.prolanv.com